

Interactive Display

CDX-86i Datasheet

SPECKTRON



OPS Pc
Module



50 Point
Touch



Wireless
Sharing



Interactive Display

CDX-86i Datasheet

SPECKTRON

DISPLAY	
Screen Type	D-LED
Aspect Ratio	16:9
Size	86 inch
Resolution	3840(H) x 2160(V)
Response Time	8ms
Refreshing Frequency	60Hz
Display colour	1.07B (10bit)
Pixel Pitch	0.4935mm x 0.4935mm
Brightness	450cd/m ²
Contrast Ratio (Dynamic)	5000:1
Viewing Angle	178° (H/V)
Lifetime	100,000 hours
TOUCH SYSTEM	
System	Windows 10/11, Linux, Mac, Chrome, Android
Sensing Type	Infrared recognition - 50 points
Gesture Support	Yes
Response Time	<5 ms
Accuracy	1mm
Communication Mode	Full-speed USB
Interface	USB
Surface Hardness	Toughened Glass with Level 9 of Mohs Standard 32767 x 32767
Output Coordinates	
DIISPLAY CONNECTORS	
HDMI-In / VGA-In	2 / 1
Audio In / Out	1 / 1
USB 2.0 / USB 3.0	3 / 2
USB-C (Data Only)	2
USB Touch	2
SPDIF	1
RS232	1
Lan Port (RJ45)	2
TF Card	1
ANDROID SYSTEM	
SKU	DSCDX86IE5
OS	Android 14
RAM	8GB
ROM	13228GGBB / 128GB*

WIRELESS	
Wi-Fi	Wi-Fi 6E
Bluetooth	5.2
Speaker Type	Built-in Speaker
Output Power	20W X 2
POWER	
Power Requirements	100-240V ~50/60Hz
Standby Power	0.5W
Overall Power (nominal power)	<400W
PC MODULE (Optional)	
Type	Detachable PC module
Model	CT-22 Series
Model	Intel®Core™ i5 /i7
CPU	8 GB / 16 GB Optional
RAM	256 GB / 512 GB Optional
SSD	Intel Iris Xe Graphics
Graphics	Intel Gigabit Ethernet
Networking	802.11ac (2.4 GHz/5 GHz)
Wi-Fi	5.2
Bluetooth	1
USB Type-C 2.0	
USB 3.2 / 2.0	2 / 2
LAN (RJ45)	1 1 /
HDMI Out / DP Out	1 1 /
Line Out / Mic In	1
PHYSICAL SPECIFICATIONS	
Dimension(L x H x D)	1953.96*1173.62*90.6
Dimension (package) L x W x H	mm 2160*1335*230 mm
Net Weight	67 Kg 98 Kg 800 x 400
Gross Weight VESA	mm
ENVIRONMENTAL CONDITIONS	
Operating Temperature	
Operating Humidity	0 C - 40 C
Storage Temperature	10% - 80%
Storage Humidity	-10 C - 45 C
	5% - 90%
Camera / Mic	48MP / 6 Array

Disclaimer: The product specifications, designs and solutions are subject to change without prior notice

www.sephorainfo.com